

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended): A device for hanging up an object, comprising two at least partially overlapping and substantially parallel elements which are movable with respect to each other, wherein spring force is provided by an intrinsic property of a material of the device such that the object is held between the elements, wherein one of the elements is at ~~it's~~ a surface thereof facing the other element provided with a thickening, wherein the first element extends upwardly, and wherein the end of the first element is positioned at a short distance from a top rim of the device.
2. (original): A device according to claim 1, wherein the material comprises a resilient plastics material.
3. (original): A device according to claim 1, wherein the parallel elements are flat.
4. (currently amended): A device according to claim 1, wherein the ~~device~~ thickening comprises a spring element which clamps to the object to be hung between the parallel elements.
5. (original): A device according to claim 1, wherein the parallel elements are each connected to a third element, said third element is provided at a side of the first parallel element that faces away from the second parallel element or at the side of the second parallel element that faces away from the first parallel element.

6. (original): A device according to claim 1, wherein during use a surface of the third element facing away from the parallel elements is a fastening surface; wherein the first parallel element along a bottom rim is attached to the third element and extends upwardly; and wherein the second parallel element along the top rim is attached to the third element and extends downwardly, substantially parallel to the first parallel element.

7. (original): A device according to claim 6, wherein the first parallel element along the bottom rim is attached pivotably and resiliently, and the second parallel element is attached along the top rim pivotably and resiliently.

8. (currently amended): A device according to claim 5, wherein with respect to the third element, ~~the one of the parallel elements which is positioned outwardly is bent at its free end outwardly~~ one of the first or second parallel elements is positioned outwardly and has a free end which is bent away from the third element.